

h/p/cosmos cardiology

h/p/cosmos mercury lt med 4.0



[Illustration non-binding]

pos.	qty.	order number	product description	price
01	1	cos0C897080000	Running machine h/p/cosmos mercury med lt 4.0 Running surface 150 x 50 cm, Speed 0 ... 22 km/h, Elevation 0 ... 24 %, Drive motor 2.2 kW Interface port COM1 for PC, ECG, Ergospirometry-, Blood-pressure system or printer - compatible to most of the systems worldwide, incl. software h/p/cosmos para control for device control, without UserTerminal Optional: with user terminal (6 keys, 6 displays) for control also without PC / ECG, running machine h/p/cosmos mercury med 4.0 (surcharge)	
02	1	cos11456	Handrails short (surcharge)	
03	1	cos00098010025	2nd Interface port COM2 for PC, ECG-, Ergospirometry-, Blood-pressure system or printer	
04	2	cos00097010034	Interface cable RS232, 5 m	
05	1	cos10223	Potential equalization cable, 5 m (required for medical systems)	
06	1	cos00097010017	Transport in cardboard box (assembled or part-assembled), installation and instruction included	

System h/p/cosmos cardiology [without ECG]

E & OE. Subject to alterations without prior notice. System- and Software-training as well as workshops on request. Special accessories and custom made running machines for special applications on request. Manufacturer: h/p/cosmos sports & medical gmbh, Am Sportplatz 8, DE 83365 Nussdorf-Traunstein / Germany, phone + 49 / 8669 / 86 42 0, fax + 49 / 8669 / 86 42 49
sales@h-p-cosmos.com www.h-p-cosmos.com

running machine:	h/p/cosmos mercury lt med 4.0 treadmill ergometer with user terminal (no Display, no Keyboard) For remote control via RS232 only.
applications:	running for sports, sports medicine, cardiology, stress tests & medicine
running surface:	length 150 cm / 59.05", width 50 cm / 19.68", access height 18 cm - special size on request - shock load reduction for the joints - belt surface with non slippery material - max. permissible load: 200kg (440 lbs)
speed range:	0 ... 22.0 km/h / 0 ... 6.1 m/sec. / 0 ... 13.6 mph special speed up to 30 km/h on request
acceleration:	7 levels (in 3 ... 131 sec. from 0 to max. speed) also for deceleration
elevation:	0 ... 24 % (0 ... 13.5°) adjustable electr., resolution 0.1 % (-24 % ... +24 % when using the reverse belt rotation) special elevation on request, electronic motor break system prevents from accelerating when running at max. elevation
running direction:	switch for reversing running belt direction, (option extra charge) safety-harness required for reverse
motor system:	2.2 kW (3.0 HP) 3phase A.C. motor (maintenance free)
power transmission:	Poly-V-Belt drive (very quiet operation)
safety systems:	CE0123, MDD, Guideline 93/42 EEC for med. devices IEC EN 60335-1 (VDE 0700); IEC EN 60601-1 (VDE 0750) IEC EN 60601-1-2 (EMC approval); IEC EN 60601-1-4 VDE 0701; VDE 0751; EN 957-1; EN 957-6; emergency-off-switch (mains cut), Potential-Equalization Transformer for Potential-Isolation from the mains.
data (resolutions):	6 displays, 4 LED for operation mode, (available via RS232 20 LEDs: display of units, profile no, steps,etc. interface for PC & speed (0.1km/h or m/sec or m/min or mph), time(00:00), para control software) in hours, minutes & seconds, elevation(0.1 %/ °), distance (1 meter ... 999.9 km or miles), METS (1MET), program step/number,energy (1 kJ/kcal), fitness index (1), power (1 Watt), heart rate (1 bpm/beat per minute)
heartrate monitoring:	POLAR wireless, 1-channel receiver, (option extra charge) ECG-accurate, measuring & display beat to beat
heartrate control:	automatic control of speed & elevation according (option extra charge) to programmed target heart rate („cardio mode“)
interface digital:	1 x RS232 COM1 incl. PC-, CosCom-, Blood-Pressure- Monitor-,ECG-, Ergospirometry- & series printer protocol (optional 2nd RS232 interface COM2: extra charge)
programs:	20 programs & profiles - 6 exercise profiles (scalable, 131 variations) - 10 test profiles (UKK Walktest, Cooper, Conconi, Graded Test etc.) - 4 free defineable profiles, 10 steps each
free PC software:	h/p/cosmos para control for display & remote control.
software:	h/p/cosmos para graphics & para analysis. (extra charge) PC software for monitoring, recording & control
colour of frame:	grey aluminium RAL 9007 (powder coated), other colours available on request
handrails:	steel tube handrails on both sides, open shape to the front
voltage supply:	220/240 Volt, 50/60 cycles (Hz), 1 phase AC, 15 Amps special voltage supply available on request
size of frame:	length 210 cm / 82.67", width 82 cm / 32.28", height 106 cm / 53.53"
weight:	approx. 200 kg / 440 lbs
E&OE. Subject to alterations without prior notice. Further details & accessories on request.	

Authorised h/p/cosmos dealer